





4 - 5 SERIES: 4.2 K - 5.2 K

<http://tiny.cc/4seriesEN>

(*) 5.2 K




Model	4.2 K	5.2 K
Engine	Kubota D722 - 3 cyl. - 719 cc.	Kubota D902 - 3 cyl. - 898 cc.
Emission Standard	Stage V and Tier 4 Final	
Power (Iso Gross) / Torque	20 HP / 45.8 Nm @ 2600 rpm	25 HP / 55 Nm @ 2400 rpm
Fuel	Diesel	
Transmission	Hydrostatic	
Drive speed (max.) ⁽¹⁾	14 km/h (8.7 mph)	
Aux. hydraulics oil flow	36 l/min (9.5 GPM)	
Max. lifting height	2,75 m (108 in)	
Tipping load, max. ⁽²⁾	1100 kg (2425 lbs)	1110 kg (2447 lbs)
Lifting capacity straight, max. ⁽³⁾	880 kg (1940 lbs)	890 kg (1962 lbs)
Breakout force / 50 cm (19.7 in)	800 kg (1764 lbs)	
Pushing force (c)	900 kgf (900 kp)	
Average ground pressure (w/standard tires)	878 kg/m ² (180 lbs/sqft)	905 kg/m ² (185 lbs/sqft)
Turning radius: inside/outside	890/1890 mm (35/74.4 in)	
Standard tires (Tractor profile)	23x8.50-12	
Weight	990 kg (2190 lbs)	1020 kg (2250 lbs)
Product Code	C944001	C977017

⁽¹⁾ Maximum speed that can be achieved with the largest diameter tires available, on a flat surface and machine without attachments.

⁽²⁾ Tipping limit, when the machine is straight, with rear weights and boom lifted just off the ground. Weight of attachment included.

⁽³⁾ Maximum load that can be lifted just off the ground when the machine is straight and with rear weights. Weight of attachment is included.

Note: Refer to the Operator's manual for the comprehensive load diagram.



Tires size	Height	Width
23x8.50-12	1960 mm (77.2 in)	980 mm (38.6 in)
23x10.50-12 ET-25	1960 mm (77.2 in)	1090 mm (42.9 in)
27x8.50-15	2010 mm (79.1 in)	1000 mm (39.4 in)
26x12.00-12 ET-50	1998 mm (78.6 in)	1200 mm (47.2 in)

FEATURES

- Kubota D722, 3 cyl. - 719 cc. or Kubota D902, 3 cyl. - 898 cc diesel engine, water cooled, electric start, glow plug
- Stage V and Tier 4 Final compliant engine
- Unbreakable Body Panels
- Hydraulic oil cooler
- Hydraulically pilot operated variable displacement drive pump
- Hydraulic multiconnector
- Double-H telescopic boom (only for 5.2 K with self-levelling)
- 4-functions joystick
- ROPS-FOPS Level I
- LCD graphic display with programmed service
- 4WD hydrostatic Direct Drive motors, proportional servo control
- 2 front working light
- Ergonomic heated seat with armrests and seat belt, adjustable position
- Mechanical parking brake
- High efficiency wheel motors
- Dynamic Block System (DBS) (5.2 K only)

4 - 5 SERIES - OPTIONS

Options	Code
110 V engine block heater	C885255
220 V engine block heater	C885250
2" Hitch receiver (not compatible with C883047)	C883062
3 additional working halogen light	C883064
3 additional working LED light	C883018
Additional front hydraulic outlets (5.3 K only)	C883503
Attachment coupling plate for rear mounting (not compatible with C883047)	C880031
Backup warning beeper	C883021
Beacon light	C883039
Biodegradable oil	C883058
DBS for 4.2 K	C883402
Driver area cover	C880049
Flat face coupling kit	C880221
Floating boom valve	C885223
Floating boom valve for 4.2 K without self-leveling boom	C883401
Fully enclosed cab with sound insulation linen	C883510
GPS tracker	C883075
Heating system	C883073
Left protection bar for operator	C885026
Mirrors	C880081
Multifunction joystick (4.2 K and 5.2 K only)	C883061
Multifunction joystick with ACI (4.2 K and 5.2 K only)	C883080
Polycarbonate back window (smart cabin)	C883508
Polycarbonate right side (smart cabin)	C883507
Polycarbonate windscreen (smart cabin)	C883506
Rear 12V electric socket	C883022
Rear bull bar (not compatible with C883062, C885014 and C880031)	C883047
Rear hydraulic outlets - double	C883502
Rear hydraulic outlets - single	C883501

4 - 5 SERIES - OPTIONS

Options	Code
Rear side weights 80 kg (40 kg + 40 kg) / 176 lbs (88 lbs + 88 lbs)	C883076
Rear weights 180 kg (90 kg + 90 kg) / 396 lbs (198lbs + 198 lbs)	C880054
Skid tires 27x8.50-15, set of 4	C884011
Snow chains for wheels 23x10.50-12, set of 2	C880046
Snow chains for wheels 23x8.50-12, set of 2	C880041
Snow chains for wheels 26x12.00-12, set of 2	C880042
Tie down bracket on wheel hub, set of 4	C883068
Torque divider	C883600
Tractor tires 23x10.50-12 ET-25, set of 4	C884007
Tractor tires 23x8.50-12, set of 4	C884005
Tractor tires 26x12.00-12 ET-50, set of 4	C884009
Trailer coupling (not compatible with C883047)	C885014
Turf tires 23x10.50-12 ET-25, set of 4	C884008
Turf tires 23x8.50-12, set of 4	C884006
Turf tires 26x12.00-12 ET-50, set of 4	C884010
Warning & Safety lights for road travel with mirrors	C883511
Wheel spacer 10 mm (0.4 in), set of 4 (max. 2 pcs for wheel)	C880090
Wheel spacer 55 mm (2.2 in), set of 4 (max. 1 pcs for wheel)	C885010
ACI Upgrade (4.2 K and 5.2 K only)	C090027
EU Certificate of Conformity (CoC) for road approval (5.2 K and 5.3 K only)	COC